



TRISOMET® U-VALUES

135mm Core = 0.15 W/m<sup>2</sup> K.  
120mm Core = 0.16 W/m<sup>2</sup> K.  
100mm Core = 0.20 W/m<sup>2</sup> K.  
80mm Core = 0.25 W/m<sup>2</sup> K.  
60mm Core = 0.33 W/m<sup>2</sup> K.  
40mm Core = 0.46 W/m<sup>2</sup> K.

Psi & f-Factor Head	Psi & f-Factor Cill
Y = 0.614W/mK.	Y = 0.613W/mK.
f = 0.735	f = 0.878

STATED CALCULATION RESULTS ARE DEPENDENT ON COMPONENTS BEING AS SHOWN  
Computer Modelled in Accordance with EN ISO 10211



Tata Steel retain the right to ammend the construction and technical specifications shown on this drawing without prior notice.

**TATA STEEL**

OFFICE TEL: 01244 892199  
TECHNICAL TEL: 01244 892133 / 34

[www.tatasteelconstruction.com](http://www.tatasteelconstruction.com)

PROJECT  
**TRISOMET® HORIZONTAL WALL DETAILS**

TITLE  
**WINDOW HEAD AND CILL**

DRAWN BY	GMc	SCALE	NTS
APPROVED BY	JCA	TOLERANCES	-
DATE	14/01/09	DRG. No.	E5-011-03-C

All support steelwork  
by others