

### Declaration of Performance

according to The Construction Products (Amendment etc) (EU Exit) Regulation 2020 No 1359)

Unique ID code

**No. TSUK D35 load bearing RoofDek  
D35, 0.70, 0.90 & 1.20 mm, S220GD, HPS200 Colorcoat  
Ultra  
(component specification TQ 000-06-035-B)**

Harmonised

standard Intended

**According to EN 1090-1:2009+A1:2011**

use-

Load bearing RoofDek

Manufacturer

Tata Steel UK Limited  
Shotton Works,  
Deeside, Flintshire,  
CH5 2NH  
Tel: +44 (0)1244 892199  
Website : www.tatasteelurope.com

Authorised  
Representative

Mark Denys - Quality Director.  
Tata Steel  
Wenckebachstraat 1 .  
Velsen Noord . 1951 JZ . NL .  
PO Box 10.000 .  
IJmuiden  
1970 . CA. NL

System of  
AVCP

System of assessment and verification of constancy of performance of the product  
System 2+

Notified Body LRQA Verification Limited, 1 Trinity Park, Bickenhill, Birmingham, B37 7ES, UK No. 0038 performed the inspection of the manufacturing plant, factory production control, the continuous surveillance assessment and evaluation. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued under the sole responsibility of Tata Steel UK limited

Signed for and on behalf of the manufacturer by:-



Jo Evans - Director, Building System UK  
Tata Steel UK

Limited

Sensitivity: general

### Declared Performance/s

| Essential characteristic             | Performance               | Harmonised technical specification |
|--------------------------------------|---------------------------|------------------------------------|
| Tolerances on dimensions and shape   | EN 1090-2 clause 11.2.2.3 | EN 1090-1:2009+A1:2011             |
| Weldability                          | NPD                       |                                    |
| Fracture toughness                   | NPD                       |                                    |
| Reaction to fire                     | A1                        |                                    |
| Release of cadmium and its compounds | NPD                       |                                    |
| Emission of radioactivity            | NPD                       |                                    |
| Durability                           | NPD                       |                                    |
| Execution class (EXC)                | EXC4                      |                                    |
| Structural characteristics - Design: | NPD                       |                                    |

# UK CA

0038 / CPR / LR00002892

Tata Steel  
Strip Products UK

0038

TSUK D35 load bearing RoofDek

EN 1090-1:2009+A1:2011

D35 Load bearing RoofDek profile

To be used in - Load bearing Roof Deck

|   |               |
|---|---------------|
| Geometrical data (tolerances in dimensions and shape) | EN 1090-2     |
| Weldability   | NPD           |
| Fracture toughness of structural steel products       | NPD           |
| Reaction to fire                                      | Class C s2 d0 |
| Release of cadmium and its compounds                  | NPD           |
| Emission of radioactivity                             | NPD           |
| Durability  | NPD           |
| Execution class (EXC)                                 | EXC 4         |
| Structural characteristics -Design:                   | NPD           |

Date:- 20/03/2023