

Vetex[®]

P4 energy absorbing terminal

The Vetex P4 energy absorbing terminal offers improved efficiency in installation and is 100% UK designed, tested and manufactured.

This innovative, short, narrow and light-weight design provides full P4 performance with single and double sided barriers in a simple kit which minimises installation time and maximises efficiency. It has been impact tested to DD ENV 1317-4:2002 Performance Class P4.



Key features

- Terminal length 8.25m
- Terminal length to Vetex 9.5m
- Maximum head width 0.3m
- Component lengths less than 5.0m

Connectivity

The terminal will be offered with connectivity to single and double sided barriers in the performance range of N2 W1 to N2 W5 including:

- Tata Steel Vetex N2 barrier
- Tata Steel Protect 365[®] N2 barrier
- TCB N2 barrier
- OBB N2 barrier

Finishes

All systems are provided as hot dip galvanised to BS EN ISO 1461 and can provide a service life of 20+ years (dependent upon conditions in accordance with specifications for Highways Works Series 400).

Please refer to our Vetex P4 energy absorbing terminal installation, maintenance and repair manual for further information.

Tata Steel
Construction Products

Llanwern Works
Newport, NP19 4QZ
United Kingdom
T: +44 (0) 1633 752191
E: cep.sales@tatasteelurope.com

English Language DUK0418:PDF:EN:0319

www.tatasteelurope.com

While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel Europe Limited, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading.

Copyright 2019
Tata Steel Europe Limited