



Declaration of Performance

(according to Regulation EU No 305/2011)

Unique ID code Forcon® 235JRH [Grade S235JRH / 1.0039]

Harmonised standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.

Manufacturer TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands
Website: www.tatasteelnederland.com

System of AVCP System of assessment and verification of constancy of performance of the product
System 2+ (FPC Certificate No: 0343/CPR/RQA2007001/A)

Notified body Notified body No. 0343
LRQA Nederland B.V.
George Hintzenweg 77
3068 AX Rotterdam
Netherlands

Table 1 – Essential characteristics and declared performances			
Essential characteristic	Performance		Harmonised technical specification
Yield strength	Nominal thickness (mm)	Values Min (MPa)	EN 10219-1:2006
	≤ 16	235	
Tensile strength	Nominal thickness (mm)	Values (MPa)	EN 10219-1:2006
	≤ 16	min 360 max 510	
Elongation (longitudinal)	Nominal thickness (mm)	Values min (%)	EN 10219-1:2006
	≤ 16	24 (22 or 17 where Table A.3 Note b applies)	
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	EN 10219-1:2006
	JRH	≤ 16	
Weldability (CEV)	Nominal thickness (mm)	Impact Value min. average (J) at Test Temp (°C)	EN 10219-1:2006
	≤ 16	27J at +20°C	
Durability	Nominal thickness (mm)	Values max (%)	EN 10219-1:2006
	≤ 16	0.35	
	Nominal thickness (mm)	Composition (cast) max.	EN 10219-1:2006
	≤ 16	C: 0.17 Mn: 1.40 P: 0.040 S: 0.040 N: 0.009	
		FF deoxidation (a)	EN 10219-1:2006
		Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating	
Tolerances on dimensions and shape	Round, square, and rectangular hollow sections	In accordance with EN 10219-2:2006	

Notes: (a) FF – Fully killed steel containing nitrogen binding elements

CE

0343

TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

Forcon® 235JRH [Grade S235JRH / 1.0039]

EN 10219-1:2006

To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.

Performance declared for the following essential characteristics:

Yield strength: 235 MPa

Tensile strength: 360 – 510 MPa

Elongation: 24% (22% or 17% where Table A.3.b applies)

Impact strength: 27J at +20°C

Weldability (CEV): 0.35%

Durability: See Declaration of Performance

Tolerances on dimensions and shape: In accordance with EN 10219-2:2006

Dangerous Substances: No Performance Determined (NPD)

DocuSigned by:

BBAC84320D6F4EC...

Jacob Gerkema

Managing Director

Tata Steel Nederland Tubes B.V.

Souvereinstraat 35, Oosterhout, 4903 RH

Netherlands

Date 04/09/2025



Declaration of Performance

(according to The Construction Products (Amendment etc.) (EU Exit) Regulations SI 2020-1359)

Unique ID code	Forcon® 235JRH [Grade S235JRH / 1.0039]		
Designated standard	EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)		
Intended use	To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.		
Manufacturer	TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands Website: www.tatasteelnederland.com		
System of AVCP	System of assessment and verification of constancy of performance of the product System 2+ (FPC Certificate No: 0038/CPR/RQA20070001/A)		
Approved body	Approved body No. 0038 LRQA Verification Ltd. 1 Trinity Park, Bickenhill Lane Solihull, West Midlands Birmingham B37 7ES United Kingdom		

Table 1 – Essential characteristics and declared performances			
Essential characteristic	Performance		Harmonised technical specification
Yield strength	Nominal thickness (mm)	Values Min (MPa)	EN 10219-1:2006
	≤ 16	235	
Tensile strength	Nominal thickness (mm)	Values (MPa)	EN 10219-1:2006
	≤ 16	min 360 max 510	
Elongation (longitudinal)	Nominal thickness (mm)	Values min (%)	EN 10219-1:2006
	≤ 16	24 (22 or 17 where Table A.3 Note b applies)	
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	Impact Value min. average (J) at Test Temp (°C)
	JRH	≤ 16	27J at +20°C
Weldability (CEV)	Nominal thickness (mm)	Values max (%)	EN 10219-1:2006
	≤ 16	0.35	
Durability	Nominal thickness (mm)	Composition (cast) max.	EN 10219-1:2006
	≤ 16	C: 0.17 Mn: 1.40 P: 0.040 S: 0.040 N: 0.009 FF deoxidation (a)	
Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating			
Tolerances on dimensions and shape	Round, square, and rectangular hollow sections	In accordance with EN 10219-2:2006	

Notes: (a) FF – Fully killed steel containing nitrogen binding elements

DocuSigned by:

BBAC84320D6F4EC...

Jacob Gerkema
Managing Director
Tata Steel Nederland Tubes B.V.
Souvereinstraat 35, Oosterhout, 4903 RH
Netherlands

Date 04/09/2025

 0038	<p>TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands 25 Forcon® 235JRH [Grade S235JRH / 1.0039]</p>
EN 10219-1:2006	<p>To be used in metal structures or in composite metal and concrete structures. This product is supplied with a non-specific inspection document 2.2 (according to EN 10204) that does not include the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is only suitable for intended uses for which the non-specific inspection 2.2 is sufficient.</p> <p>Performance declared for the following essential characteristics:</p> <p>Yield strength: 235 MPa Tensile strength: 360 – 510 MPa Elongation: 24% (22% or 17% where Table A.3.b applies) Impact strength: 27J at +20°C Weldability (CEV): 0.35% Durability: See Declaration of Performance Tolerances on dimensions and shape: In accordance with EN 10219-2:2006</p> <p>Dangerous Substances: No Performance Determined (NPD)</p>