



Declaration of Performance

(according to Regulation EU No 305/2011)

Unique ID code	Forcon® TT 355J0H [Grade S355J0H / 1.0547]
Harmonised standard	EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)
Intended use	To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.
Manufacturer	TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands Website: www.tatasteelnederland.com
System of AVCP	System of assessment and verification of constancy of performance of the product System 2+ (FPC Certificate No: 0343/CPR/RQA2007001/A)
Notified body	Notified body No. 0343 LRQA Nederland B.V. George Hintzenweg 77 3068 AX Rotterdam Netherlands

Table 1 – Essential characteristics and declared performances				
Essential characteristic	Performance		Harmonised technical specification	
Yield strength	Nominal thickness (mm)	Value min (MPa)	EN 10219-1:2006	
	≤ 16	355		
Tensile strength	Nominal thickness (mm)	Values (MPa)		
		min		
	< 3	510		
Elongation	Nominal thickness (mm)	max		
		680		
	≥ 3 ≤ 16	470		
Impact strength (longitudinal)	Nominal thickness (mm)	Value min (%)		
		long.		
	≤ 16	20 (18 where Table A.3, Note c applies)		
Weldability (CEV)	Grade	Nom. Thk. (mm)		
	J0H	≤ 16		
Durability	Nominal thickness (mm)	Impact Value min. average (J) at Test Temp (°C)		
		≤ 16	27J at 0°C	
		≤ 16	Value max (%)	
		≤ 16	0.45	
		Composition (cast) (max unless otherwise shown)		
		≤ 16	C: 0.22 Si: 0.55 Mn: 1.60 P: 0.035 S: 0.035	
		≤ 16	FF deoxidation (a)	
		Durability is also dependent on any method of protection subsequently applied to the hollow section and the type and thickness of the coating employed.		
		Round, square and rectangular hollow sections	In accordance with EN 10219-2:2006	
		Tolerances on dimensions and shape		
		Notes: (a) FF – Fully killed steel containing nitrogen binding elements		

DocuSigned by:

BBAC84320D6F4EC...

Jacob Gerkema

Managing Director

Tata Steel Nederland Tubes B.V.

Souvereinstraat 35, Oosterhout, 4903 RH

Netherlands

Date 04/09/2025

CE

0343

TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

Forcon® TT 355J0H [Grade S355J0H / 1.0547]

EN 10219-1:2006

To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Performance declared for the following essential characteristics:

Yield strength: 355 MPa

Tensile strength: 470 – 630 MPa (≥ 3 mm)

Elongation: 20% (18% where Table A.3.c applies)

Impact strength: 27J at 0°C

Weldability (CEV): 0.45%

Durability: See Declaration of Performance

Tolerances on dimensions and shape: In accordance with EN 10219-2:2006

Dangerous Substances: No Performance Determined (NPD)



Declaration of Performance

(according to The Construction Products (Amendment etc.) (EU Exit) Regulations SI 2020-1359)

Unique ID code	Forcon® TT 355J0H [Grade S355J0H / 1.0547]	
Designated standard	EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)	
Intended use	<p>To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.</p>	
Manufacturer	<p>TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands Website: www.tatasteelnederland.com</p>	
System of AVCP	System of assessment and verification of constancy of performance of the product System 2+ (FPC Certificate No: 0038/CPR/RQA20070001/A)	
Approved body	<p>Approved body No. 0038 LRQA Verification Ltd. 1 Trinity Park, Bickenhill Lane Solihull, West Midlands Birmingham B37 7ES United Kingdom</p>	

Table 1 – Essential characteristics and declared performances			
Essential characteristic	Performance		Harmonised technical specification
Yield strength	Nominal thickness (mm)	Value min (MPa)	EN 10219-1:2006
	≤ 16	355	
Tensile strength	Nominal thickness (mm)	Values (MPa)	
		min	max
	< 3	510	680
Elongation	Nominal thickness (mm)	Value min (%)	
		long.	
	≤ 16	20 (18 where Table A.3, Note c applies)	
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	
	J0H	≤ 16	Impact Value min. average (J) at Test Temp (°C)
Weldability (CEV)	Nominal thickness (mm)	Value max (%)	
		≤ 16	0.45
Durability	Nominal thickness (mm)	Composition (cast) (max unless otherwise shown)	
		C: 0.22 Si: 0.55 Mn: 1.60 P: 0.035 S: 0.035	
	≤ 16	FF deoxidation (a)	
		Durability is also dependent on any method of protection subsequently applied to the hollow section and the type and thickness of the coating employed.	
	Tolerances on dimensions and shape	Round, square and rectangular hollow sections	In accordance with EN 10219-2:2006

Notes: (a) FF – Fully killed steel containing nitrogen binding elements

 0038 TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands 25 Forcon® TT 355J0H [Grade S355J0H / 1.0547]
EN 10219-1:2006
<p>To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.</p> <p>Performance declared for the following essential characteristics:</p> <p>Yield strength: 355 MPa Tensile strength: 470 - 630 MPa (≥ 3 mm) Elongation: 20% (18% where Table A.3.c applies) Impact strength: 27J at 0°C Weldability (CEV): 0.45% Durability: See Declaration of Performance Tolerances on dimensions and shape: In accordance with EN 10219-2:2006</p> <p>Dangerous Substances: No Performance Determined (NPD)</p>

DocuSigned by:

BBAC84320D6F4EC...

Jacob Gerkema

Managing Director

Tata Steel Nederland Tubes B.V.

Souvereinstraat 35, Oosterhout, 4903 RH
Netherlands

Date 04/09/2025