



Declaration of Performance

(according to Regulation EU No 305/2011)

Unique ID code Forcon® TT 355K2H [Grade S355K2H / 1.0512]

Harmonised standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Manufacturer TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout,
4903 RH, Netherlands
Website: www.tatasteelnederland.com

System of AVCP System of assessment and verification of constancy of performance of the product
System 2+ (FPC Certificate No: 0343/CPR/RQA2007001/A)

Notified body Notified body No. 0343
LRQA Nederland B.V.
George Hintzenweg 77
3068 AX Rotterdam
Netherlands

DocuSigned by:

BBAC84320D6F4EC...

Jacob Gerkema
Managing Director
Tata Steel Nederland Tubes B.V.
Souvereinstraat 35, Oosterhout, 4903 RH
Netherlands

Date 04/09/2025

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance		Harmonised technical specification
Yield strength	Nominal thickness (mm)	Values min (MPa)	EN 10219-1:2006
	≤16	355	
Tensile strength	Nominal thickness (mm)	Values (MPa)	EN 10219-1:2006
	< 3	min 510 max 680	
Elongation	Nominal thickness (mm)	Values min (%)	EN 10219-1:2006
	≥3 ≤16	long. 20 ≤16 (18 where Table A.3 Note c applies)	
Impact strength (longitudinal)	Grade	Nom. Thk. (mm)	EN 10219-1:2006
	K2H	≤16	
Weldability (CEV)	Nominal thickness (mm)	Impact Value min, average (J) at Test Temp (°C)	EN 10219-1:2006
	≤16	40J at - 20°C	
Durability	Nominal thickness (mm)	Values max (%)	EN 10219-1:2006
	≤16	0.45	
Durability	Nominal thickness (mm)	Composition (cast) (max. unless otherwise shown)	EN 10219-1:2006
	≤16	C: 0.22 Si: 0.55 Mn: 1.60 P: 0.030 S: 0.030	
Durability		FF deoxidation (a)	EN 10219-1:2006
		Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating	
Tolerances on dimensions and shape	Round, square and rectangular hollow sections	In accordance with EN 10219-2:2006	

Notes: (a) FF – Fully killed steel containing nitrogen binding elements



0343

TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

Forcon® TT 355K2H [Grade S355K2H / 1.0512]

EN 10219-1:2006

To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Performance declared for the following essential characteristics:

Yield strength: 355 MPa

Tensile strength: 470 – 630 MPa (≥ 3 mm)

Elongation: 20% (18% where Table A.3.c applies)

Impact strength: 40J at - 20°C

Weldability (CEV): 0.45%

Durability: See Declaration of Performance

Tolerances on dimensions and shape: In accordance with EN 10219-2:2006

Dangerous Substances: No Performance Determined (NPD)



Declaration of Performance

(according to The Construction Products (Amendment etc.) (EU Exit) Regulations SI 2020-1359)

Unique ID code	Forcon® TT 355K2H [Grade S355K2H / 1.0512]
Designated standard	EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)
Intended use	To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.
Manufacturer	TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands Website: www.tatasteelnederland.com
System of AVCP	System of assessment and verification of constancy of performance of the product System 2+ (FPC Certificate No: 0038/CPR/RQA2007001/A)
Approved body	Approved body No. 0038 LRQA Verification Ltd. 1 Trinity Park, Bickenhill Lane Solihull, West Midlands Birmingham B37 7ES United Kingdom

DocuSigned by:

BBAC84320D6F4EC...

Jacob Gerkema
Managing Director
Tata Steel Nederland Tubes B.V.
Souvereinstraat 35, Oosterhout, 4903 RH
Netherlands

Date 04/09/2025

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance		Harmonised technical specification
Yield strength	Nominal thickness (mm)	Values min (MPa)	EN 10219-1:2006
	≤16	355	
Tensile strength	Nominal thickness (mm)	Values (MPa)	EN 10219-1:2006
	≤ 3	min 510 max 680	
Elongation	≤3 ≤16	470 630	EN 10219-1:2006
	Nominal thickness (mm)	Values min (%) long.	
Impact strength (longitudinal)	≤16	20 (18 where Table A.3 Note c applies)	EN 10219-1:2006
	Grade Nom. Thk. (mm)	Impact Value min. average (J) at Test Temp (°C)	
Weldability (CEV)	K2H ≤16	40J at - 20°C	EN 10219-1:2006
	Nominal thickness (mm)	Values max (%)	
Durability	≤16	0.45	EN 10219-1:2006
	Nominal thickness (mm)	Composition (cast) (max. unless otherwise shown)	
	≤16	C: 0.22 Si: 0.55 Mn: 1.60 P: 0.030 S: 0.030	EN 10219-1:2006
		FF deoxidation (a)	
Tolerances on dimensions and shape		Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating	
Tolerances on dimensions and shape		Round, square and rectangular hollow sections	In accordance with EN 10219-2:2006

Notes: (a) FF – Fully killed steel containing nitrogen binding elements

UK CA 0038
TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands
25
Forcon® TT 355K2H [Grade S355K2H / 1.0512]
EN 10219-1:2006
To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.
Performance declared for the following essential characteristics:
Yield strength: 355 MPa
Tensile strength: 470 – 630 MPa (≥ 3 mm)
Elongation: 20% (18% where Table A.3.c applies)
Impact strength: 40J at - 20°C
Weldability (CEV): 0.45%
Durability: See Declaration of Performance
Tolerances on dimensions and shape: In accordance with EN 10219-2:2006
Dangerous Substances: No Performance Determined (NPD)