



Declaration of Performance (according to Regulation EU No 305/2011)

Unique ID code TSNT 355MH [Grade S355MH / 1.8845]

Harmonised standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Manufacturer TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands
Website: www.tatasteelnederland.com

System of AVCP System of assessment and verification of constancy of performance of the product
System 2+ (FPC Certificate No: 0343/CPR/RQA2007001/A)

Notified body Notified body No. 0343
LRQA Nederland B.V.
George Hintzenweg 77
3068 AX Rotterdam
Netherlands

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance		Harmonised technical specification	
	Nominal thickness (mm)	Values min (MPa)		
Yield strength	≤ 16	355	EN 10219-1:2006	
	Tensile strength	≤ 16		Values min (MPa)
min max				
Elongation	≤ 16	Values min (%)		
		long.		
Impact strength (longitudinal)	Grade MH	Nom. Thk. (mm) ≤ 16		Impact Value min. average (J) at Test Temp (°C)
				40J at - 20°C
Weldability (CEV)	Nominal thickness (mm)	≤ 16		Values max (%)
				0.39
Durability	Nominal thickness (mm)	≤ 16		Composition (cast) (max. unless otherwise shown)
			C 0.14	
			Si 0.50	
			Mn 1.50	
			P 0.035	
			S 0.030	
			Nb 0.050	
			V 0.10	
			Al 0.020 min.	
			Ti 0.050	
			Ni 0.30	
			Mo 0.20	
			N 0.020	
			GF deoxidation (a)	
			Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating	
Tolerances on dimensions and shape	Round, square and rectangular hollow sections		In accordance with EN 10219-2 2006	

Notes: (a) GF – Fully killed fine grain steel containing nitrogen binding elements



0343

TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

TSNT 355MH [Grade S355MH / 1.8845]

EN 10219-1:2006


To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Performance declared for the following essential characteristics:
Yield strength: 355 MPa
Tensile strength: 450 – 610 MPa
Elongation: 22% (20% where Table B.5.a applies)
Impact strength: 40J at - 20°C
Weldability (CEV): 0.39%
Durability: See Declaration of Performance
Tolerances on dimensions and shape: In accordance with EN 10219-2 2006

Dangerous Substances: No Performance Determined (NPD)

Jacob Gerkema
Managing Director
Tata Steel Nederland Tubes B.V.
Souvereinstraat 35, Oosterhout, 4903 RH
Netherlands

Date 09/01/2025

DocuSigned by:

BBAC84320D6F4EC...



Declaration of Performance

(according to The Construction Products (Amendment etc.) (EU Exit) Regulations SI 2020-1359)

Unique ID code TSNT 355MH [Grade S355MH / 1.8845]

Designated standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Manufacturer TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands
Website: www.tatasteelnederland.com

System of AVCP System of assessment and verification of constancy of performance of the product System 2+ (FPC Certificate No: 0038/CPR/RQA20070001/A)

Approved body Approved body No. 0038
LRQA Verification Ltd.
1 Trinity Park, Bickenhill Lane
Soliuhull, West Midlands
Birmingham
B37 7ES
United Kingdom

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance		Harmonised technical specification
	Nominal thickness (mm)	Values min (MPa)	
Yield strength	≤ 16	355	EN 10219-1:2006
	Tensile strength	≤ 16	
450 610			
Elongation	≤ 16	Values min (%) long.	
		22 (20 where Table B.5, Note a applies)	
Impact strength (longitudinal)	Grade	Impact Value min. average (J) at Test Temp (°C)	
	MH ≤ 16	40J at - 20°C	
Weldability (CEV)	Nominal thickness (mm)	Values max (%)	
	≤ 16	0.39	
Durability	≤ 16	Composition (cast) (max. unless otherwise shown)	
		C 0.14	
		Si 0.50	
		Mn 1.50	
		P 0.035	
		S 0.030	
		Nb 0.050	
		V 0.10	
		Al 0.020 min.	
		Ti 0.050	
		Ni 0.30	
		Mo 0.20	
		N 0.020	
		GF deoxidation (a)	
	Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating		
Tolerances on dimensions and shape	Round, square and rectangular hollow sections	In accordance with EN 10219-2 2006	

Notes: (a) GF – Fully killed fine grain steel containing nitrogen binding elements



0038

TATA STEEL NEDERLAND TUBES BV
Registered in Netherlands No. 20022812
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

TSNT 355MH [Grade S355MH / 1.8845]

EN 10219-1:2006


To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Performance declared for the following essential characteristics:
Yield strength: 355 MPa
Tensile strength: 450 – 610 MPa
Elongation: 22% (20% where Table B.5.a applies)
Impact strength: 40J at - 20°C
Weldability (CEV): 0.39%
Durability: See Declaration of Performance
Tolerances on dimensions and shape: In accordance with EN 10219-2 2006

Dangerous Substances: No Performance Determined (NPD)

Jacob Gerkema
Managing Director
Tata Steel Nederland Tubes B.V.
Souvereinstraat 35, Oosterhout, 4903 RH
Netherlands

Date 09/01/2025

DocuSigned by:

 BBAC84320D6F4EC...