



## Declaration of Performance

(according to Regulation EU No 305/2011)

Unique ID code TSNT TT420MH [Grade S420MH / 1.8847]

Harmonised standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)

Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Manufacturer TATA STEEL NEDERLAND TUBES BV  
Registered in Netherlands No. 20022812  
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands  
Website: [www.tatasteelnederland.com](http://www.tatasteelnederland.com)

System of AVCP System of assessment and verification of constancy of performance of the product  
System 2+ (FPC Certificate No: 0343/CPR/RQA2007001/A)

Notified body Notified body No. 0343  
LRQA Nederland B.V.  
George Hintzenweg 77  
3068 AX Rotterdam  
Netherlands

**Jacob Gerkema**  
Managing Director  
Tata Steel Nederland Tubes B.V.  
Souvereinstraat 35, Oosterhout, 4903 RH  
Netherlands

Date 09/01/2025

DocuSigned by:

BBAC84320D6F4EC...

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance		Harmonised technical specification	
	Nominal thickness (mm)	Value min (MPa)		
Yield strength	≤ 16	420	EN 10219-1: 2006	
	Nominal thickness (mm)	Values (MPa)		
Tensile strength	≤ 16	min 500 max 660		
	Nominal thickness (mm)	Value min (%)		
Elongation	≤ 16	19 (17 where Table B.5, Note a applies)		
	Grade	Impact Value min. average (J) at Test Temp (°C)		
Impact strength (longitudinal)	MH	40J at -20°C		
	Nominal thickness (mm)	Value max (%)		
Weldability (CEV)	≤ 16	0.43		
	Nominal thickness (mm)	Composition (cast) (max. unless otherwise shown)		
Durability	≤ 16	C: 0.16 V: 0.12 Si: 0.50 Al: 0.020 min. Mn: 1.70 Ti: 0.050 P: 0.035 Ni: 0.30 S: 0.030 Mo: 0.20 Nb: 0.050 N: 0.020		
		GF deoxidation (a)		
	Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating			
Tolerances on dimensions and shape	Rectangular sections		Circular sections	
	Outside dimensions	H, B < 100 mm	0.5% min. = 0.25 mm (b)	± 0.5% min. = ± 0.25 mm max. = ± 5 mm (b)
		H, B ≤ 200 mm	0.4% (b)	
		H, B > 200 mm	0.3% (b)	
	Thickness	EN 10219-2 (c)	EN 10219-2 (c)	
	Out-of-roundness (for D/T < 100)	Not applicable	1% (b)	
	Concavity/convexity	0.4% min. = 0.25 mm (b)	Not applicable	
	Squareness of side	90° ± 0.5° (b)	Not applicable	
	External corner profile	T ≤ 6.0	2T ± 0.2T (or 1.8T to 2.2T) (b)	Not applicable
		6.0 < T ≤ 10.0	2.5T ± 0.25T (or 2.25T to 2.75T) (b)	
T > 10.0		3T ± 0.3T (or 2.7T to 3.3T) (b)		
Twist	EN 10219-2 (c)	Not applicable		
Straightness	EN 10219-2 (c)	EN 10219-2 (c)		
Mass per unit length	EN 10219-2 (c)	EN 10219-2 (c)		
Length	EN 10219-2 (c)	EN 10219-2 (c)		

Notes:

- (a) GF – Fully killed steel containing nitrogen binding elements
- (b) The declared tolerance is half of the maximum allowed by EN 10219-2:2006
- (c) The declared tolerance is the maximum allowed by EN 10219-2:2006



0343

TATA STEEL NEDERLAND TUBES BV  
Registered in Netherlands No. 20022812  
Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

TSNT TT420MH [Grade S420MH / 1.8847]

EN 10219-1:2006

**To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.**

**Performance declared for the following essential characteristics:**

**Yield strength:** 420 MPa

**Tensile strength:** 500 – 660 MPa

**Elongation:** 19% (17% where Table B.5.a applies)

**Impact strength:** 40J at -20°C

**Weldability (CEV):** 0.43%

**Durability:** See Declaration of Performance

**Tolerances on dimensions and shape:** See Declaration of Performance

**Dangerous Substances:** No Performance Determined (NPD)



### Declaration of Performance

(according to The Construction Products (Amendment etc.) (EU Exit) Regulations SI 2020-1359)

Unique ID code TSNT TT420MH [Grade S420MH / 1.8847]  
 Designated standard EN 10219-1:2006 - Cold formed welded structural hollow sections of non-alloy and fine grain steels - Part 1: Technical delivery conditions (issued on the Official Journal of the European Union on 01/02/2007)  
 Intended use To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.  
 Manufacturer TATA STEEL NEDERLAND TUBES BV Registered in Netherlands No. 20022812 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands Website: [www.tatasteelnederland.com](http://www.tatasteelnederland.com)  
 System of AVCP System of assessment and verification of constancy of performance of the product System 2+ (FPC Certificate No: 0038/CPR/RQA20070001/A)  
 Approved body Approved body No. 0038 LRQA Verification Ltd. 1 Trinity Park, Bickenhill Lane Solihull, West Midlands Birmingham B37 7ES United Kingdom

Jacob Gerkema  
 Managing Director  
 Tata Steel Nederland Tubes B.V.  
 Souvereinstraat 35, Oosterhout, 4903 RH  
 Netherlands

Date 09/01/2025

DocuSigned by:  
  
 BBAC84320D6F4EC...

Table 1 – Essential characteristics and declared performances

Essential characteristic	Performance		Harmonised technical specification	
	Value	Value		
Yield strength	Nominal thickness (mm)	Value min (MPa)	EN 10219-1: 2006	
	≤ 16	420		
Tensile strength	Nominal thickness (mm)	Values (MPa)	EN 10219-1: 2006	
	≤ 16	min 500 max 660		
Elongation	Nominal thickness (mm)	Value min (%)	EN 10219-1: 2006	
	≤ 16	long. 19 (17 where Table B.5, Note a applies)		
Impact strength (longitudinal)	Grade	Impact Value min. average (J) at Test Temp (°C)	EN 10219-1: 2006	
	Nom. Thk. (mm)	40J at -20°C		
Weldability (CEV)	Nominal thickness (mm)	Value max (%)	EN 10219-1: 2006	
	≤ 16	0.43		
Durability	Nominal thickness (mm)	Composition (cast) (max. unless otherwise shown)	EN 10219-1: 2006	
	≤ 16	C: 0.16 V: 0.12 Si: 0.50 Al: 0.020 min. Mn: 1.70 Ti: 0.050 P: 0.035 Ni: 0.30 S: 0.030 Mo: 0.20 Nb: 0.050 N: 0.020 GF deoxidation (a)		
Durability is also dependent on any method of protection subsequently applied and the type and thickness of the coating				
Tolerances on dimensions and shape	Rectangular sections		Circular sections	
	Outside dimensions	H, B < 100 mm	0.5% min. = 0.25 mm (b)	± 0.5% min. = ± 0.25 mm max. = ± 5 mm (b)
		H, B ≤ 200 mm	0.4% (b)	
		H, B > 200 mm	0.3% (b)	
	Thickness	EN 10219-2 (c)	EN 10219-2 (c)	
	Out-of-roundness (for D/T < 100)	Not applicable	1% (b)	
	Concavity/convexity	0.4% min. = 0.25 mm (b)	Not applicable	
	Squareness of side	90° ± 0.5° (b)	Not applicable	
	External corner profile	T ≤ 6.0	2T ± 0.2T (or 1.8T to 2.2T) (b)	Not applicable
		6.0 < T ≤ 10.0	2.5T ± 0.25T (or 2.25T to 2.75T) (b)	
T > 10.0		3T ± 0.3T (or 2.7T to 3.3T) (b)		
Twist	EN 10219-2 (c)	Not applicable		
Straightness	EN 10219-2 (c)	EN 10219-2 (c)		
Mass per unit length	EN 10219-2 (c)	EN 10219-2 (c)		
Length	EN 10219-2 (c)	EN 10219-2 (c)		

Notes:

- (a) GF – Fully killed steel containing nitrogen binding elements
- (b) The declared tolerance is half of the maximum allowed by EN 10219-2:2006
- (c) The declared tolerance is the maximum allowed by EN 10219-2:2006



0038

TATA STEEL NEDERLAND TUBES BV  
 Registered in Netherlands No. 20022812  
 Registered office: Souvereinstraat 35, Oosterhout, 4903 RH, Netherlands

25

TSNT TT420MH [Grade S420MH / 1.8847]

EN 10219-1:2006

To be used in metal structures or in composite metal and concrete structures. This product is supplied with a specific inspection document 3.1 (according to EN 10204) that includes the full length non-destructive testing of the weld (as defined in table 2 of EN 10219-1). This product is suitable for being used as constituent product of a steel structure according to EN 1090. Table 1 of EN 1090-2:2018 requires a 3.1 inspection document for structural steel above S275.

Performance declared for the following essential characteristics:

Yield strength: 420 MPa

Tensile strength: 500 – 660 MPa

Elongation: 19% (17% where Table B.5.a applies)

Impact strength: 40J at -20°C

Weldability (CEV): 0.43%

Durability: See Declaration of Performance

Tolerances on dimensions and shape: See Declaration of Performance

Dangerous Substances: No Performance Determined (NPD)